

Nanotech Surface Solutions™ Anti-Graffiti Shield +

Product Information

Description

- A unique one-pack, white spirit based, external coating designed to give effective protection against both graffiti and fly-poster attack and is a semi-transparent/clear liquid
- GraffitiProtection is a permanent not a sacrificial system, allowing for repeated easy removal of any graffiti attacks.
- Graffiti Protection is available in matte or glossy finish and has been specifically designed to minimize any alteration to the appearance of the coated surface.

Suitable Substrates

- Graffiti Protection is suitable for a wide variety of surfaces.
- The matt version is particularly effective on normally difficult-to-protect substrates such as rough brick or textured finishes.
- GraffitiProtection can be used on concrete, render, masonry, porous stone, timber and previously painted surfaces.

Other Data

- Spread rate: 8 square metres; less on a porous substrate.
- The drying time: 1 – 3 hours, depending on conditions.
- Re-coat interval: between 2 and 4 hours.
- Application temperature: minimum 5^oC.
- Working time: approximately 30 to 90 minutes. Due to the moisture curing nature of the product do not leave containers open.
- Equipment: take care to clean equipment immediately after use, however some rollers and brushes may need to be disposed of.
- Shelf Life: 12 months in unopened container.
- UV Resistance: Excellent.

Application

- Stir contents thoroughly before application.
- Apply two coats of Graffiti Protection at the suggested spread rate to obtain optimum results, by brush, roller or spray. If spraying, take care to avoid overspray as this may damage surrounding property.
- Porous surfaces should be sealed with Anti-Graffiti Shield Plus's non-darkening sealer which also acts as a non-darkening sealer on substrates that will darken when coated directly with Anti-Graffiti Shield Plus.